

NAUTICA





BLEND OIL OUTBOARD 2T

DESCRIZIONE

OUTBOARD 2T è un lubrificante senza ceneri per motori fuoribordo a due tempi raffreddati ad acqua, che soddisfa le specifiche della Boating Industry Association (B.I.A.). È un prodotto formulato particolarmente per minimizzare l'imbrattamento della candela, i fenomeni di pre-accensione, prevenire la ruggine e ridurre l'usura del motore anche quando esso venga fatto funzionare con miscela povera di olio.

DESCRIPTION

OUTBOARD 2T is a lubricant ashless outboard two-stroke water-cooled, that meets the specifications of the Boating Industry Association (BIA). It's a product especially formulated to minimize the contamination of the spark plug, the phenomena of pre-ignition, prevent rust and reduce engine wear even when it is operated with lean oil.

SPECIFICHE

NMM TC-W III

PACKAGING

250 MI

500 MI

1 Lt pz. 12

5 Lt pz. 4

20 Lt

60 Lt.

208 Lt.



BLEND OIL OUTBOARD 2T SYNTH

DESCRIZIONE

OUTBOARD 2T SYNTH è un olio sintetico per motori fuoribordo a due tempi.

Risponde alla specifica NMMA TC-W3, garantendo in tal modo un eccezionale potere lubrificante e protezione da incollamento fasce e grippaggi. Assicura elevatissime prestazioni.

DESCRIPTION

OUTBOARD 2T SYNTH is a synthetic oil for two-stroke outboard engines.

It meets the NMMA TC-W3 specification, thus ensuring exceptional lubricating power and protection from sticking bands and seizures. It ensures very high performance.

SPECIFICHE

NMMA TC-W III,
ISO-L-EGD,
JASO FD

PACKAGING

250 MI

500 MI

1 Lt pz. 12

5 Lt pz. 4

20 Lt

60 Lt.

208 Lt.



Blend  **oIL**

INDUSTRIA LUBRIFICANTI